



# PYRO SHIELD, INC.

Insulation, Fabrication and Warehouse • FREE Local Delivery

[www.PyroShield.com](http://www.PyroShield.com)



**PROTECT YOUR INVESTMENT**  
Pyro Shield Heat Barrier Solutions

PYRO SHIELD 2012 | ALL RIGHTS RESERVED

## PS 2200 KEVLAR DATA SHEET

### About the Product

Pyro Shield's PS 2200 Kevlar is an aramid fiber blend over a fiberglass core yarn. The major applications for this product include high temperature covers and sleeves.

### Product Info

Fabric: Aramid fiber blend

Color: Yellow

Coating: None

Weight: 22 oz / y<sup>2</sup> +/- 10 % oz / yd<sup>2</sup>

Thickness: 0.08 in +/- 0.001 in

Temperature Resistance: 600°F

Count: 20 x 11

Tensile Strength: WARP: 225 lbs / inch

FILL: 150 ends / inch

\*\*\*All statements are expressed opinion which we believe to be accurate, reliable, and presented without guarantee or responsibility on our part. The data presented above consists of typical properties and should not be used in preparing specifications. No warranties are expressed or implied and users should test this material thoroughly for their specific application.\*\*\*

(219) 661-8600 • Fax: (219) 661-8612  
1171 E. Erie Court • Crown Point, IN 46307  
FREE Local Delivery

General Questions  
or Quotes Contact  
[sales@pyroshield.com](mailto:sales@pyroshield.com)

(281) 941-9054 • Fax: (281) 941-4437  
1424 Sens Road Unit 3 • LaPorte, TX 77571  
FREE Local Delivery in Houston Area